



BYZON[™]
C H E M I C A L S

Brighten Up
Your Tiles With
Multi **Colored Grout.**

SHADE **CARD**

TILE GROUT



TILECARE EP-100



BYZON TILECARE EP-100 Epoxy Tile Grout is a three-component color-fast, chemical resistant, hard wearing, impervious epoxy tile joint filler and is 100% stain-proof. It effectively fills the gaps between tiles to give a hard-wearing, dust-proof tile joint. It is well suited for residential and commercial installations where materials must resist physical abuse, shock, and chemical aggression.

AREA OF APPLICATION

- Institutional kitchens
- Cafeterias
- Institutional facilities
- Swimming pools
- Rest rooms
- Schools

FEATURES & BENEFITS

- Stainfree
- Colour - fast
- Easy to install and clean
- Chemical and temperature resistant
- Non-cracking or powdering
- Water cleanable when fresh


HOW TO USE

- 01** Mix resin & hardener thoroughly in desired ration.
- 02** Add filler gradually while mixing, until homogeneous paste is obtained.
- 03** Fill the joint with the help of rubber float.
- 04** Clean the tiles with wet sponge within 30 Minutes for best results.


TILECARE EP-100

**EPOXY
GROUT**

30 shade available



401 - White




402 - Ivory



403 - Almond



404 - Burgundy




405 - Silver



406 - Sauterne



407 - Mocha



408 - Hemp



409 - Sand Stone



410 - Smoke Grey



411 - Sunrise Pink



412 - Pastel Brown



413 - Sky Blue



414 - Golden Yellow



415 - Jet Black


TILECARE EP-100

**EPOXY
GROUT**

30 shade available



416 - Terracotta



417 - Sable



418 - Marble Beige



419 - Coffee Brown



420 - Buff



421 - Anthracite



422 - Steel Grey



423 - Light Grey



424 - Dark Grey



425 - Natural stone



426 - Platinum



427 - Moss Green



428 - Aqua Blue



429 - Jesalmer Gold



430 - Italian Red

TILECARE CG-100

**CEMENTITIOUS
GROUT**

20 shade available



201 - White



202 - Ivory



203 - Hemp



204 - Marble Beige



205 - Brown



206 - Sunrise Pink



207 - Jet Black



208 - Sky Blue



209 - Aqua Blue



210 - Steel Grey



211 - Light Grey



212 - Dark Grey



213 - Coffee Brown



214 - Terracotta



215 - Buff

216 - Sauterne217 - Natural Stone218 - Dark Brown219 - Jesalmer220 - Moss Green

GROUTCARE



BYZON GROUTCARE is a blend of polymeric emulsion to be added in BYZON cementitious grout to enhance the strength and durability of the grout when applied between tile and stone in internal and external areas under wet and dry conditions on wall and floors.

FEATURES & BENEFITS

- Enhances compressive strength of cementitious grout.
- BYZON GROUTCARE mixed with BYZON cementitious grout can be used in joints between 1-8 mm.
- Improves performance of cementitious grouts, enhancing compressive strength, flexibility, crack resistance & water tightness, while reducing shrinkage.

PACK SIZE

- 200ml, 500ml, 1 Ltr, 5 Ltr, 10 Ltr & 20 Ltr Pack

Health & safety: Use of gloves and goggles is recommended. Any splashes to the skin or eyes should be washed off with clean water. In the event of prolonged irritation, medical advice should be sought.

Disclaimer: Grout Shades are approximate guide only, actual shade and texture will depend on jobsite conditions. User are advised to undertake a trial for product suitability prior to its full scale usage. There is no express or implied guarantee / warranty for the results. The company is not liable for any consequential damages.

TILECARE CG-100



TILECARE CG-100 is a polymer-modified, cement-based tile joint filler grouting material, which is highly suitable for filling the joints/gap of all types of tiles. It exhibits water-resistant properties, making it an Ideal choice for various applications.

AREA OF APPLICATION

- For filling tile joints in bathrooms, kitchens, internal & external floor & wall tiles. Joins upto 5mm width tiles.

FEATURS & BENEFITS

- Easy to use & clean – just mix with water, ready to use
- Polymer modified – crack-free, minimum shrinkage & water resistance
- Suitable for varied tile and stones – all ceramics, vitrified tiles, granites, etc.
- Low VOC – for healthy living
- For interior & exterior use


HOW TO USE

- 01** Add 1 part of water to 3 parts powder by volume. Mix well to get a smooth and uniform paste.
- 02** After the initial set of the material (2 hrs) remove the excess material on the tile edges with a wet cloth or damp sponge.
- 03** Wait up to 24 Hrs. After 24 Hrs you can allow the foot Traffic.



BYZONTM

CHEMICALS

 Plot No. 3, Survey No. 149/2, Shivam Industrial Zone-1,
Kalavad Road, At. Chhapra, Ta. Lodhika,
Dist. Rajkot - 360021

 +91 908 1000 760

 byzonchemicals@gmail.com

 www.byzon.net

Follow Us On



Scan This Qr Code For
Product Information &
Technical Data For Our
Complete Product Range